



A Study of Near-Source Earthquake Ground Motions of Three California Earthquakes: Northridge, Whittier, and Landers

1. 2000年10月	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日
2. 2000年10月	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日
3. 2000年10月	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日
4. 2000年10月	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日
5. 2000年10月	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日
6. 2000年10月	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日
7. 2000年10月	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日
8. 2000年10月	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日
9. 2000年10月	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日
10. 2000年10月	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日	2000年10月1日

19980303 021

Prepared for Headquarters, U.S. Army Corps of Engineers

The contents of this report are not to be used for advertising, publication, or promotional purposes. Citation of trade names does not constitute an official endorsement or approval of the use of such commercial products.

The findings of this report are not to be construed as an official Department of the Army position, unless so designated by other authorized documents.



PRINTED ON RECYCLED PAPER

A Study of Near-Source Earthquake Ground Motions of Three California Earthquakes: Northridge, Whittier, and Landers

by David J. Leeds

David J. Leeds and Associates
11972 Chalon Road
Los Angeles, CA 90049

Final report

Approved for public release; distribution is unlimited


DMC QUALITY INSPECTED 3

Prepared for U.S. Army Corps of Engineers
Washington, DC 20314-1000

Monitored by U.S. Army Engineer Waterways Experiment Station
3909 Halls Ferry Road, Vicksburg, MS 39180-6199



**US Army Corps
of Engineers**
Waterways Experiment
Station



FOR INFORMATION CONTACT:
PUBLIC AFFAIRS OFFICE
U.S. ARMY ENGINEER
WATERWAYS EXPERIMENT STATION
3909 HALLS FERRY ROAD
VICKSBURG, MISSISSIPPI 39180-6199
PHONE: (601) 634-2502

Waterways Experiment Station Cataloging-in-Publication Data

Leeds, David J.

A study of near-source earthquake ground motions of three California earthquakes : Northridge, Whittier, and Landers / by David J. Leeds ; prepared for U.S. Army Corps of Engineers ; monitored by U.S. Army Engineer Waterways Experiment Station.

68 p. : ill. ; 28 cm. — (Contract report ; GL-98-2)

Includes bibliographical references.

1. Earthquake intensity. 2. Earthquakes — California — Northridge. 3. Earthquakes — California — Whittier. 4. Earthquakes — California — Landers. I. United States. Army. Corps of Engineers. II. U.S. Army Engineer Waterways Experiment Station. III. Geotechnical Laboratory (U.S. Army Engineer Waterways Experiment Station) IV. Title. V. Series: Contract report (U.S. Army Engineer Waterways Experiment Station) ; GL-98-2. TA7 W34c no.GL-98-2

Contents

Preface	iv
Foreword	v
Problem	1
Historical Horizontal Accelerations	1
Historical Vertical Accelerations	2
Other Studies	2
Procedure	3
Report	3
Personnel	3
Schedule	4
Database	4
Vertical/Horizontal Ground Motion Ratios	7
Recommendations	8
Conclusions	8
References	9
Figures:	
Group 1. Named Faults and Stations	
Group 2. Ground Motion	
Group 3. Ground Motion Adjusted for Site and Structure	
Group 4. Ground Motion with NEHRP Adjustment	
Group 5. Ground Motion with NEHRP Plus Structure Adjustment	

Preface

This report was sponsored by the U.S. Army Corps of Engineers in the Army Civil Works Earthquake Engineering Research Program (EQEN). This study is part of ongoing EQEN research regarding geological-seismological evaluation of earthquake hazards.

The report was prepared by Mr. David J. Leeds, Consultant, Los Angeles, CA, under contract No. DACW39-96-M-1349 and was monitored by the Geotechnical Laboratory (GL), U.S. Army Engineer Waterways Experiment Station (WES). Dr. W. F. Marcuson III was Director, GL.

At the time of publication of this report, Director of WES was Dr. Robert W. Whalin. Commander was COL Robin R. Cababa, EN.

Foreword

This report should be utilized with the following points in mind.

■ Site conditions at the majority of strong-motion accelerograph stations are poorly known, even to the operators of the stations. Geologic and geotechnic parameters of many of the stations used in this report are derived from gross geologic maps and may be hopelessly inadequate. Some few however are known with great detail. No qualitative evaluation of the site classifications are given.

■ Maximum accelerations from many of the stations are unprocessed (Vol. I) values. Later publications may slightly change the values.

■ There is debate with respect to the use of maximum acceleration as an index of damage potential. Consideration has been given to an "effective" acceleration wherein high frequency peaks are clipped, as well as the use of maximum velocity as a parameter.

■ Epicenter locations, depths of focus, and magnitudes may vary dependent upon reevaluation of the data, as well as data set used. Menlo Park, Pasadena, and Berkeley may differ slightly in their calculations. The differences are not significant to this study.

■ Fault locations, specially buried thrust faults, are still in a state of flux. The scales used preclude precise locations. The scheme used is the most recent released by the Southern California Earthquake Center (SCEC).

■ The contouring program used leaves decisions outside the control of the operator. That is, there is no personal bias in any of the contouring.

■ The reader must carefully scrutinize the data to evaluate the site characteristics of the recording station. All stations are used in these plots, from freefield to second basement.

■ New ideas are continually emerging. Geomorphic control of ground shaking and the effect of pressure ridges (Reidel ridges) have only recently been recognized.

Problem:

Earthquake ground motion, in engineering terms, usually has only a single descriptor: maximum peak horizontal acceleration. The acquisition of large suites of near-source ground motion data and developing analyses suggests the utility of further exploitation of the data.

Current practice has failed to recognize the effect of strong vertical motions, a weakness demonstrated by the many column failures in the recent Northridge Earthquake. Also, there has not previously been as large a suite of strong-motion records where this component had such high values.

Earthquake mechanisms, site conditions, and topography are important and must be considered. There are also differences between basement and nearby freefield recordings which require compatibility adjustments of basement records where freefield recordings are not available.

Isoseismal maps traditionally plot only the reported intensity. This report utilizes the large suite of recorded accelerations, plotting both the recorded as well as "adjusted" data. The adjustments have the effect of "leveling the playing field," providing more stations suitable for ground motion studies.

Historical Horizontal Accelerations:

Acceleration recordings began in late 1932 in the Los Angeles area of Southern California under the auspices of the U.S. Coast and Geodetic Survey. Even these earliest accelerograms indicated that peak ground motions were greater than the design levels used by engineers. As the years passed and more instruments were fielded, higher and higher accelerations were recorded. The most significant event at which near-source ground motions were "captured" was the Northridge Earthquake of January 17, 1994. Exploitation of these data, and their application to engineering design, is essential. Table HHA shows this increase of horizontal recorded ground motion over time:

TABLE HHA. HISTORICAL HORIZONTAL ACCELERATIONS

Date	Earthquake	Mag.	Dist (km)	Site	Horizontal Accel, g
1933	Long Beach	6.2	10	Soft	0.19
1940	El Centro	7.1	9	Soft	0.33
1966	Parkfield	5.6	31	Soft	0.48
1971	San Fernando	6.5	9	Rock	1.15
1980	Mammoth Lakes	6.3	14	---	0.99
1984	Morgan Hill	6.2	25	Franciscan	1.29
1985	Nahanni, Canada				0.91
1987	Whittier	5.9	1	Firm	0.54
1992	Cape Mendocino	7.1	4	Rock	>1.8
1992	Landers/Big Bear	6.5	11	Al/Gn	0.57
1993	Coalinga, Aft.				0.82
1994	Northridge	6.7	5	Soft	1.82

Historical Vertical Accelerations:

Vertical acceleration recordings have also increased in values with time, but their effect has forcibly been brought to our attention only recently. See Table HVA.

TABLE HVA. HISTORICAL VERTICAL ACCELERATIONS

Date	Earthquake	Mag.	Dist (km)	Site	Vertical Accel, g
1971	San Fernando, Pacoima Dam	6.5	9	Rock	0.72
1976	Gazli, USSR	7.3	10?	Hard	1.30
1978	Tabbas, Iran	7.4	3	Soft	0.88
1979	Imp. Valley: Sta.6	6.6	1	Soft	1.74
1980	Mexicali Vict. Sta	6.4	0	Soft	1.00
1985	Nahanni, NWT	6.9	8	Hard	>2.00
1992	Landers, CA	7.5	22	Soft	0.20
1992	Petrolia, Cape M.	7.1	4	Rock	>1.85
1994	N'ridge, Tarzana	6.7	5	Al/Si	1.18
1994	N'ridge, Pac. Dam	6.7	17	Rock	1.40

These tables, and the lists of less well known earthquakes, show that large motions are not isolate events but are common to the epicentral areas of shallow focus earthquakes of magnitudes approaching 6 and over.

Other Studies:

Several published articles or reports are germane to the present report (see References). Isoseismal (intensity) maps of the Northridge earthquake have been published by Dewey et al. (1995). Borchardt (ms.1994) displayed a horizontal isoacceleration map in early 1994. Horizontal isoacceleration maps have been published by Stewart et al. (1995). Preliminary isoacceleration maps, both horizontal and vertical using USC data only, were published by Todorovska et al. (February 1994). The data of Borchardt (USGS) and of Todorovska (USC) were available to the present study. The papers by Dewey et al. and by Stewart et al. were published after our plots were complete.

Procedure:

- Task 1: Isoacceleration maps have been prepared for three recent, large Southern California Earthquakes:
 - Northridge, January 17, 1994
 - Landers, June 28, 1992
 - Whittier, October 1, 1987.

The isoseismal maps have been prepared using the as-reported (raw) data for horizontal and vertical components of motion, and with several iterations making adjustment for site conditions, freefield/basement/structure relationships, and response to NEHRP criteria. Values for the individual points have been processed to accommodate these influencing factors.

- Task 2: The final isoacceleration maps are overlain on structural geologic maps with recent fault locations.

- Task 3: Interpretation considers the following:

Recording site conditions

Horizontal and vertical motions with respect to magnitude, fault types, and distance from fault sources

Spectral content and predominant period

Scaling to possible larger and smaller earthquakes

Report:

The report presents our conclusions with respect to fault mechanisms, earthquake magnitudes, distance from sources, and site conditions.

Representative horizontal and vertical accelerograms with their spectra are presented.

Personnel:

The study was conducted by David J. Leeds, Principal. Assistance in computer contouring was by Dr. Larry Porter. We are also indebted to Mr. Tom Solemio (formerly of ANCO Engineers) for other computer assistance. There has been consultation with other prominent geologists/seismologists in interpretation and fault locations.

Schedule:

Delays were encountered in the acquisition of certain of the strong-motion data. There was a long delay for important Northridge Earthquake records. Many of the "Code" stations as of the date of this report are still not available. The "Code" stations for the City of Los Angeles have not routinely been collected. Some have recovered by the California Division of Mines and Geology and other contractors. Their targets for completion of this project have not been met; however, we believe there is sufficient data to finalize the database.

Database:

Suites of strong-motion accelerograph records from three recent Southern California earthquakes have been selected for analysis. The Northridge Earthquake provides the best data by far, both in the levels of motion and the quantity of data. Quality with respect to recording and data processing is satisfactory and uniform for all stations. Landers data is a bit weak in terms of nearfield stations, and Whittier does not have a large magnitude. However, this is what nature has provided.

Northridge	January 17, 1994	Ms = 6.6	34.211°N	118.538°W
Landers	June 28, 1992	M = 7.5	34.201°N	116.436°W
Whittier	October 1, 1987	ML = 6.1	34.058°N	118.075°W

TABLE I-R

Structural adjustment (multiplier).

Adjusts recording from structure to freefield.

1.0 Freefield to 3-story building (gnd/bsmt location).

1.4 4-story to high rise (ground/basement location).

These "constants" were derived from an examination of the dozen pairs of freefield/structure sets of records. There is some scatter, but a reasonably constant relationship exists between recordings at ground or basement level within the structure, and the nearby freefield record.

TABLE I-S

Site adjustment to convert to equivalent rock site:

S Soft Multiply by 0.6

F Firm Multiply by 0.8

H Hard Multiply by 0.9

R Rock Multiply by 1.0

These relationships were derived from examination of recordings at similar distance but with varying surficial geotechnical/geological conditions. Applying these adjustments converts all observations to an equivalent rock site.

TABLE I-Z

NEHRP (National Earthquake Hazards Reduction Program) site adjustments:

Converted as a multiplier of recorded motion by factors shown to normalize to "A", rock. Factor is acceleration dependent. See Geotechnical Reference.

	NEHRP	This report	Acceleration, g				
			0.1g	0.2g	0.3g	0.4g	0.5g
Hard Rock	A _o	AO	1.25	1.25	1.25	1.25	1.25
Rock	A	AA	1.00	1.00	1.00	1.00	1.00
Very stiff/gravels	B	BB	0.83	0.83	0.91	1.00	1.00
Sand, silt, clay	C	CC	0.62	0.71	0.83	0.91	1.00
Thin clay	D1	D1	0.40	0.59	0.83	1.11	1.11
Thick clay	D2	D2	0.50	0.62	0.83	1.11	1.11
Problem sites	E	EE	----	----	----	----	----

Vertical/Horizontal Ground Motion Ratios

The data for the three earthquakes has been examined with respect to the ratio of vertical to maximum horizontal acceleration. Values for each individual station are shown in Column **AQ** on the master spread sheets, Table I. The ratios in radial zones centering on the epicenters follows:

Northridge:	km, radius	No. stations	v ÷ H
	0-10	11	0.82
	11-25	50	0.61
	0-25	61	0.65
	26-50	81	0.50
	0-50	142	0.56
	51-100	199	0.40
	0-100	341	0.54
Whittier:	km, radius	No. stations	V ÷ H
	0-10	18	0.70
	11-25	33	0.58
	0-25	51	0.62
	26-50	58	0.67
	0-50	109	0.65
	51-100	75	0.50
	0-100	184	0.59
Landers:	km, radius	No. stations	V ÷ H
	0-25	4	0.84
	26-50	15	0.79
	0-50	19	0.80
	51-100	143	0.64
	0-100	162	0.66

Recommendations:

Of the three datasets used, the Northridge has by far the best potential for exploitation. Several obvious recommendations present themselves.

■ Is the complete network of almost 375 stations in the Los Angeles area Necessary? Discounting the special studies such as on highway structures, bridges, certain types of buildings, and hospitals, can the same data be obtained by fewer or relocated stations? It is recognized that each of the several networks or systems was derived with different objectives. The present compilation combines all of the published data and much unpublished data.

Since both freefield and structural data are mixed, examination should be continued to establish a confidence level for the use of structural data in ground-motion studies. Are the factors used in this report acceptable? What is acceptable? What records from different types of structure can be equated with freefield?

Each of the several types of instrumental locations should be plotted separately to examine variation of recorded motion due to location in a structure.

Each of the three major network datasets should be independently plotted and compared. Once a confidence level is ascribed to the structural stations, then redeployment of some of the freefield stations should provide improved coverage.

■ Past geological/geotechnical evaluations have tended to lump stations into a few categories, with "alluvium" hiding a host of variations. Also, location with respect to buried thrust faults and Reidel folds has not been a consideration. Recognition, and targeting, of these three conditions is a necessity if we are ever able to understand near-source ground motion.

■ Much more needs to be known about instrumental site conditions. This need not require deep borings and geophysics for every site. Our knowledge of sites has not kept up with the proliferation of instrumentation. The expense of instrumentation of one major structure (approximately \$50,000) is about the cost of adequate preliminary site descriptions of about 200 stations. It would certainly raise the confidence level in the use of accelerograph data.

■ A comprehensive (combined) catalogue of strong-motion stations is required, and assignment of standard code names to each station. This is the norm for teleseismic stations but not for strong motion.

Conclusions

1. Vertical motion is enhanced in the near-source area of high angle thrust faults such as in the Northridge earthquake.

2. Short range variation of ground motion may be explained in areas of youthful, geomorphic/tectonic folds by the effect of Reidel ridges. These areas undergoing stress exhibit higher shaking than nearby sites and are indicative of nearby active faulting.

REFERENCES

NORTHRIDGE EARTHQUAKE OF JANUARY 17, 1994

Anderson, John G., et al., (July 1981), "Los Angeles Vicinity Strong-Motion Accelerograph Network." University of Southern California Department of Civil Engineering Report No. CE 81-04. [The report shows the locations of USC accelerograph stations.]

Dewey, James W., et al., (June 1995), "Intensity Distribution and Isoseismal Maps for the Northridge, California, Earthquake of January 17, 1994." U.S. Geological Survey Open-File Report 95-92. [Gives isoseismal plots and discussion of damage distribution.]

McCarthy, Richard J. and James E. Slosson, "The Use of Seismic Hazard Maps for Improved Earthquake Risk Reduction," (ms.) Paper presented to U.S./Japan Earthquake Conference, Tokyo, May 18, 1995. Abs. Association of Engineering Geologists 1995 Annual Meeting, Sacramento, October 1995. [Paper states that "at some locations ...in the near-source area with unique local geology, shaking exceeded assumptions underlying design values..." A map relates structural and geomorphic features within near-source area.]

Naeim, Farzad (Fed. 1995), "On Seismic Design Implications of the 1994 Northridge Earthquake Records." Earthquake Spectra, Vol. 11, No. 1, pp 91-109. [Examines spectral and energy content of records.]

Porcella, R. L. et al., (Feb. 1994), "Accelerograms Recorded at USGS National Strong-Motion Network Stations During the Ms=6.6 Northridge, California Earthquake of January 17, 1994." U.S. Geological Survey Open File Report 94-141.

Shaka, A. et al. (Feb. 1994), "CSMIP Strong-Motion Records from the Northridge, California Earthquake of 28 June 1992," Office of Strong Motion Studies, California Division of Mines and Geology, Report No. OSMS 94-07.

Steward, Jonathan P., et al., (May-June 1995), "A Report on Geotechnical Aspects of the January 17, 1994 Northridge Earthquake." Seismological Research Letters, Vol. 66, No. 3, pp 7-19. [The paper shows horizontal isoacceleration and relates to damage pattern.]

Todorovska, M. I., M. D. Trifunac, and S. S. Ivanovicc (Fed. 1994), "Second Preliminary Report on Distribution of Peak Ground Accelerations During the Northridge, California, Earthquake of January 17, 1994 (Data from the Los Angeles Strong-Motion Network)," University of Southern California School of Engineering, Department of Civil Engineering. [Three page report contours horizontal and vertical accelerations from approximately 100 USC stations.]

WHITTIER EARTHQUAKE OF OCTOBER 1, 1987)

Anderson, John G. et al., (July 1981), "Los Angeles Vicinity Strong Motion Accelerograph Network," University of Southern California Department of Civil Engineering, Report No. CE 81-04. [The report shows the location of USC accelerograph stations.]

Brady, A. G., P. N. Mork, and L. C. Seekins, (Jan. 1989), "Processed Strong-Motion Records, Whittier Narrows, California Earthquake, October 1, 1987, Volume 2, Selected USGS-NSMIN Stations between 11 and 31 KM from the Epicenter and the Santa Ana River Pipeline Bridge." U.S. Geological Survey Open File Report 89-122.

California Strong-Motion Instrumentation Program, California Division of Mines and Geology (no date), "Plots of Processed Data from Cogswell Dam."

California Strong-Motion Instrumentation Program, California Division of Mines and Geology (no date), "Plots of Processed Data from Los Angeles - Vincent Thomas Bridge."

California Strong-Motion Instrumentation Program, California Division of Mines and Geology (no date), "Plots of Processed Data from Puddingstone Dam."

California Strong-Motion Instrumentation Program, California Division of Mines and Geology (no date), "Plots to Accompany Tapes: Whittier87-IB1 and IB2, Whittier87-IIB, and Whittier87-IIIB."

Etheredge, E. and R. Porcella (Oct. 1987), "Strong-Motion Data from the October 1, 1987 Whittier Narrows Earthquake," U.S. Geological Survey Open-File Report 87-616.

Huang, M. J., et al. (July 1989), "Processed Strong-Motion Data from the Whittier California Earthquake of 1 October 1987, Part I, Ground-Response Records." Office of Strong-Motion Studies, California Division of Mines and Geology, Report No. OSMS 89-03.

Levine M. B. et al. (Aug. 1988), "Accelerograms Recorded at CALTECH during the Whittier, Narrows Earthquakes of October 1 and 4, 1987: A Preliminary Report." Earthquake Engineering Research Laboratory, California Institute of Technology, Report No. EERL 88-01.

Shaka, A. F. et al. (Oct. 1987), "CSMIP Strong-Motion Records from the Whittier, California Earthquake of 1 October 1987." Office of Strong-Motion Studies, California Division of Mines and Geology, Report No. OSMS 87-05.

Switzer, J. C. and R. L. Porcella (1994), "Catalogue of U.S. Geological Survey Strong-Motion Records, 1992."

Trifunac, M. D. (Fed. 1988), "The Whittier Narrows, California Earthquake of October 1, 1987 - Note on Peak Acceleration During the 1 and 4 October Earthquakes," Earthquake Spectra, EERI, pp 101-113.

LANDERS EARTHQUAKE OF JUNE 28, 1992

Borcherdt, R. D. et al. (Dec. 1985), "A General Earthquake-Observation System (GEOS)" (abstract), Bulletin of the Seismological Society of America, pp 1783-1825.

Darragh, R. et al. (Sept. 1993), "Processed CSMIP Strong-Motion Records from the Landers and Big Bear, California Earthquakes of 28 June 1992: San Bernardino - I10/215 Interchange," Office of Strong-Motion Studies, California Division of Mines and Geology, Report No. OSMS 93-08."

Etheredge, E. et al. (Sept. 1993), "Strong-Motion Accelerograph Records from the M=7.5 Landers, California Earthquake of June 28, 1992." National Strong-Motion Program, U.S. Geological Survey, Open File Report 93-557.

Shakal, A. et al. (Aug. 1992), "CSMIP Strong-Motion Records from the Landers, California Earthquake of 28 June 1992." Office of Strong-Motion Studies, California Division of Mines and Geology, Report No. OSMS 92-09.

GEOTECHNICAL REFERENCES

Martin, Geoffrey R, and Ricardo Dobry, (Oct. 1994), Earthquake Site Response and Seismic Code Provisions." NCEER BUTTLETIN, Vol. 8, No. 4, pp 1-6. [Reviews NEHRP seismic provisions classifying soil factors used in present report.]


Note: Additional data has been supplied by Roger Borcherdt (U.S. Geological Survey), Mihailo Trifunac and Maria Todorovska (University of Southern California), Ron Tognazzini (Los Angeles Department of Water and Power), and Dennis Ostrom (Southern California Edison Company).

Group 1. Named Faults and Stations

Fig. NRDG-50
Fig. NRDG-100

Fig. WHIT-50
Fig. WHIT-100

Fig. LAND-50
Fig. LAND-100



Northridge Earthquake M=6.7 Main Shock of January 17, 1994

Stations with Maximum Horizontal Records

RADIUS OF LARGEST CIRCLE IS 100 KM

Stations - total: 348, with data: 344, without: 4, rejected: 0, in plot: 301

Map File: CALINE1.DAT

Command File: NR100HZ.GAC

Program: APCFAC2.75


Fault File: KANAMN.DAT

Station File: NRDGDIS.PRN

(Lambert conformal projection)

1995 MAY 22 03:33:52.29

Fig. NRDG-100



Whittier Earthquake M=5.9 of October 1, 1987

Stations with Maximum Horizontal Records

RADIUS OF CIRCLE IS 50 KM

Stations - total: 184, with data: 184, without: 0, rejected: 0, in plot: 116

Map File: CALINE2.DAT

Command File: WH50HZ.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: WHITDIS.PRN

(Lambert conformal projection)

1995 MAY 22 12:38:28.68

Fig. WHIT-50



Landers Earthquake M=7.5 of June 28, 1992

Stations with Maximum Horizontal Records

RADIUS OF LARGEST CIRCLE IS 100 KM

Stations - total: 162, with data: 162, without: 0, rejected: 0, in plot: 108

Map File: CALINE2.DAT

Command File: LN100HZ.GAC

Program: APGFAC2.75

Fault File: KANAMN.DAT

Station File: LANDDIS.PRN

(Lambert conformal projection)

1995 MAY 22 01:31:27.44

Fig. LAND-100

Group 2. Ground Motion

Fig. NRDG-50-NS (Col. M)
Fig. NRDG-50-V (Col. N)
Fig. NRDG-50-EW (Col. O)
Fig. NRDG-50-MAX (Col. P)

Fig. NRDG-100-V (Col. N)
Fig. NRDG-100-MAX (Col. P)


Fig. NRDG-50-NS W/O TAR
Fig. NRDG-50-V W/O TAR
Fig. NRDG-50-EW W/O TAR
Fig. NRDG-50-MAX W/O TAR

Fig. WHIT-50-NS (Col. M)
Fig. WHIT-50-V (Col. N)
Fig. WHIT-50-EW (Col. O)
Fig. WHIT-50-MAX (Col. P)

Fig. WHIT-100-V (Col. N)
Fig. WHIT-100-MAX (Col. P)

Fig. LAND-50-NS (Col. M)
Fig. LAND-50-V (Col. N)
Fig. LAND-50-EW (Col. O)
Fig. LAND-50-MAX (Cl. P)

Fig. LAND-100-V (Col. N)
Fig. LAND-100-MAX (Col. P)



Northridge Earthquake M=6.7 of January 17, 1994

Maximum North-South Acceleration

RADIUS OF CIRCLE IS 50 KM

Stations - total: 348, with data: 280, without: 68, rejected: 0, in plot: 144

Map File: CALINE2.DAT

Fault File: KANAMN.DAT

Station File: NRDGDIS.PRN


Command File: NR50NC.GAC

(Lambert conformal projection)

Program: APGFAC2.75

1995 MAY 22 04:13:43.7

Fig. NRDG-50-NS (Col. M)



Northridge Earthquake M=6.7 of January 17, 1994

Maximum Vertical Acceleration

RADIUS OF CIRCLE IS 50 KM

Stations - total: 348, with data: 344, without: 4, rejected: 0, in plot: 197

Map File: CALINE2.DAT

Command File: NR50VC.GAC


Program: APGFAC2.75

Fault File: KANAMN.DAT

Station File: NRDGDIS.PRN
(Lambert conformal projection)

1995 MAY 22 04:14:44.72

Fig. NRDG-50-V (Col. N)



Northridge Earthquake M=6.7 of January 17, 1994

Maximum East-West Acceleration

RADIUS OF CIRCLE IS 50 KM

Stations - total: 348, with data: 278, without: 70, rejected: 0, in plot: 143

Map File: CALINE2.DAT

Fault File: KANAMN.DAT

Station File: NRDGDIS.PRN


Command File: NR50EC.GAC

(Lambert conformal projection)

Program: APGFAC2.75

1995 MAY 22 04:16:25.89

Fig. NRDG-50-EW (Col. 0)



Northridge Earthquake M=6.7 of January 17, 1994

Maximum Horizontal Acceleration

RADIUS OF CIRCLE IS 50 KM

Stations - total: 348, with data: 344, without: 4, rejected: 0, in plot: 198

Map File: CALINE2.DAT

Command File: NR50HC.GAC

Program: AFGFAC2.75


Fault File: KANAMN.DAT

Station File: NRDGDIS.PRN

(Lambert conformal projection)

1995 MAY 22 04:17:34.44

Fig. NRDG-50-MAX (Col. P)



Northridge Earthquake M=6.7 of January 17, 1994

Maximum Vertical Acceleration

RADIUS OF LARGEST CIRCLE IS 100 KM

Stations - total: 348, with data: 344, without: 4, rejected: 0, in plot: 301

Map File: CALINE1.DAT

Command File: NR100VC.GAC


Program: APGFAC2.75

Fault File: KANAMN.DAT

Station File: NRDGDIS.PRN
(Lambert conformal projection)

1995 MAY 22 04:20:54.20

Fig. NRDG-100-V (Col. N)



Northridge Earthquake M=6.7 of January 17, 1994

Maximum Horizontal Acceleration

RADIUS OF LARGEST CIRCLE IS 100 KM

Stations - total: 348, with data: 344, without: 4, rejected: 0, in plot: 301

Map File: CALINE1.DAT

Fault File: KANAMN.DAT

Station File: NRDGDIS.PRN


Command File: NR100HC.GAC

(Lambert conformal projection)

Program: APGFAC2.75

1995 MAY 22 04:24:15.83

Fig. NRDG-100-MAX (Col. P)



Northridge Earthquake M=6.6 of January 17, 1994

North-South Acceleration (w/o TAR), g

RADIUS OF CIRCLE IS 50 KM

Stations - total: 348, with data: 279, without: 68, rejected: 1, in plot: 143

Map File: CALINE2.DAT

Command File: NR50NWT.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: NRDGDIS.PRN

(Lambert conformal projection)

1995 MAY 28 18:10:57.01

Fig. NRDG-50-NS w/o TAR



Northridge Earthquake M=6.6 of January 17, 1994

Vertical Acceleration (w/o TAR), g

RADIUS OF CIRCLE IS 50 KM

Stations - total: 348, with data: 343, without: 4, rejected: 1, in plot: 198

Map File: CALINE2.DAT

Command File: NR50VWT.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: NRDGDIS.PRN

(Lambert conformal projection)

1995 MAY 28 18:11:53.15

Fig. NRDG-50-V w/o TAR



Northridge Earthquake M=6.6 of January 17, 1994

East-West Acceleration (w/o TAR), g

RADIUS OF CIRCLE IS 50 KM

Stations - total: 348, with data: 277, without: 70, rejected: 1, in plot: 142

Map File: CALINE2.DAT

Command File: NR50EW.T.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: NRDGDIS.PRN

(Lambert conformal projection)

1995 MAY 28 18:12:50.10

Fig. NRDG-50-EW w/o TAR



Northridge Earthquake M=6.6 of January 17, 1994

Maximum Horizontal Acceleration (w/o TAR), g

RADIUS OF CIRCLE IS 50 KM

Stations - total: 348, with data: 343, without: 4, rejected: 1, in plot: 199

Map File: CALINE2.DAT

Command File: NR50HWT.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: NRDGDIS.PRN

(Lambert conformal projection)

1995 MAY 28 18:13:55.57

Fig. NRDG-50-MAX w/o TAR



Whittier Earthquake M=5.9 of October 1, 1987

Maximum North-South Acceleration

RADIUS OF CIRCLE IS 50 KM

Stations - total: 184, with data: 184, without: 0, rejected: 0, in plot: 116

Map File: CALINE2.DAT

Fault File: KANAMN.DAT

Command File: WH50NC.GAC


Station File: WHITDIS.PRN

Program: APGFAC2.75

(Lambert conformal projection)

1995 MAY 22 13:07:59.48

Fig. WHIT-50-NS (Col. M)



Whittier Earthquake M=5.9 of October 1, 1987

Maximum Vertical Acceleration

RADIUS OF CIRCLE IS 50 KM

Stations - total: 184, with data: 181, without: 3, rejected: 0, in plot: 114

Map File: CALINE2.DAT

Command File: WH50VC.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: WHITDIS.PRN

(Lambert conformal projection)

1995 MAY 22 13:08:56.21

Fig. WHIT-50-V (Col. N)



Whittier Earthquake M=5.9 of October 1, 1987

Maximum Horizontal Acceleration

RADIUS OF CIRCLE IS 50 KM

Stations - total: 184, with data: 184, without: 0, rejected: 0, in plot: 116

Map File: CALINE2.DAT

Command File: WH50HC.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: WHITDIS.PRN

(Lambert conformal projection)

1995 MAY 22 13:10:48.28

Fig. WHIT-50-MAX (Col. P)



Whittier Earthquake M=5.9 of October 1, 1987

Maximum Vertical Acceleration

RADIUS OF LARGEST CIRCLE IS 100 KM

Stations - total: 184, with data: 181, without: 3, rejected: 0, in plot: 178

Map File: CALINE2.DAT

Fault File: KANAMN.DAT

Station File: WHITDIS.PRN


Command File: WH100VC.GAC

(Lambert conformal projection)

Program: APGFAC2.75

1995 MAY 22 13:13:36.61

Fig. WHIT-100-V (Col. N)



Whittier Earthquake M=5.9 of October 1, 1987

Maximum Horizontal Acceleration

RADIUS OF LARGEST CIRCLE IS 100 KM

Stations - total: 184, with data: 184, without: 0, rejected: 0, in plot: 181

Map File: CALINE2.DAT

Fault File: KANAMN.DAT

Station File: WHITDIS.PRN


Command File: WH100HC.GAC

(Lambert conformal projection)

Program: APGFAC2.75

1995 MAY 22 13:16:26.44

Fig. WHIT-100-MAX (Col. P)



Landers Earthquake M=7.5 of June 28, 1992

Maximum North-South Acceleration

RADIUS OF CIRCLE IS 50 KM

Stations - total: 162, with data: 162, without: 0, rejected: 0, in plot: 28

Map File: CALINE2.DAT

Command File: LN50NC.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: LANDDIS.PRN

(Lambert conformal projection)

1995 MAY 22 04:37:27.86

Fig. LAND-50-NS (Col. M)



Landers Earthquake M=7.5 of June 28, 1992

Maximum Vertical Acceleration

RADIUS OF CIRCLE IS 50 KM

Stations - total: 162, with data: 161, without: 1, rejected: 0, in plot: 28

Map File: CALINE2.DAT

Command File: LNSOVC.GAC

Program: APCFAC2.75


Fault File: KANAMN.DAT

Station File: LANDDIS.PRN

(Lambert conformal projection)

1995 MAY 22 04:50:17.86

Fig. LAND-50-V (Col. N)



Landers Earthquake M=7.5 of June 28, 1992

Maximum East-West Acceleration

RADIUS OF CIRCLE IS 50 KM

Stations - total: 162, with data: 161, without: 1, rejected: 0, in plot: 28

Map File: CALINE2.DAT

Fault File: KANAMN.DAT

Station File: LANDDIS.PRN


Command File: LN50EC.GAC

(Lambert conformal projection)

Program: APGFAC2.75

1995 MAY 22 04:51:11.68

Fig. LAND-50-EW (Col. 0)



Landers Earthquake M=7.5 of June 28, 1992

Maximum Horizontal Acceleration

RADIUS OF CIRCLE IS 50 KM

Stations - total: 162, with data: 162, without: 0, rejected: 0, in plot: 28

Map File: CALINE2.DAT

Command File: LN50HC.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: LANDDIS.PRN

(Lambert conformal projection)

1995 MAY 22 04:52:11.55

Fig. LAND-50-MAX (Col. P)



Landers Earthquake M=7.5 of June 28, 1992

Maximum Horizontal Acceleration

RADIUS OF LARGEST CIRCLE IS 100 KM

Stations - total: 162, with data: 162, without: 0, rejected: 0, in plot: 108

Map File: CALINE2.DAT

Command File: LN100HC.GAC

Program: APCFAC2.75

Fault File: KANAMN.DAT

Station File: LANDDIS.PRN

(Lambert conformal projection)

1995 MAY 22 04:43:42.28

Fig. LAND-100-MAX (Col. P)

Group 3. Ground Motion Adjusted for Site and Structure


Fig. NRDG-Adj-50-V (Col. V)

Fig. WHIT-Adj-50-V (Col. V)

Fig. WHIT-Adj-50-MAX (Col. X)

Fig. LAND-Adj-50-V (Col. V)

Fig. LAND-Adj-50-MAX (Col. X)



Northridge Earthquake M=6.6 of January 17, 1994

Vertical Adjusted Acceleration, g

RADIUS OF CIRCLE IS 50 KM

Stations - total: 348, with data: 343, without: 5, rejected: 0, in plot: 198

Map File: CALINE2.DAT

Command File: NR50VA.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: NRGDIS.PRN

(Lambert conformal projection)

1995 MAY 28 18:14:54.73

Fig. NRDC-Adj-50-V (Col. V)



Whittier Earthquake M=6.1 of October 1, 1987

Vertical Adjusted Acceleration, g

RADIUS OF CIRCLE IS 50 KM

Stations - total: 184, with data: 184, without: 0, rejected: 0, in plot: 116

Map File: CALINE2.DAT

Command File: WH50VA.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: WHITDIS.PRN

(Lambert conformal projection)

1995 MAY 28 18:18:08.34

Fig. WHIT-Adj-50-V (Col. V)



Whittier Earthquake M=6.1 of October 1, 1987

Maximum Adjusted Horizontal Acceleration, g

RADIUS OF CIRCLE IS 50 KM

Stations - total: 184, with data: 184, without: 0, rejected: 0, in plot: 116

Map File: CALINE2.DAT

Fault File: KANAMN.DAT

Station File: WHITDIS.PRN


Command File: WH50HA.GAC

(Lambert conformal projection)

Program: APGFAC2.75

1995 MAY 28 18:19:28.75

Fig. WHIT-Adj-50-MAX (Col. X)



Landers Earthquake M=7.5 of June 28, 1992

Vertical Adjusted Acceleration, g

RADIUS OF CIRCLE IS 50 KM

Stations - total: 162, with data: 162, without: 0, rejected: 0, in plot: 29

Map File: CALINE2.DAT

Command File: LN50VA.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: LANDDIS.PRN

(Lambert conformal projection)

1995 MAY 28 18:15:50.09

Fig. LAND-Adj-50-V (Col. V)



Landers Earthquake M=7.5 of June 28, 1992

Maximum Adjusted Horizontal Acceleration, g

RADIUS OF CIRCLE IS 50 KM

Stations - total: 162, with data: 162, without: 0, rejected: 0, in plot: 29

Map File: CALINE2.DAT

Command File: LN50HA.GAC

Program: APGFAC2.75

Fault File: KANAMN.DAT

Station File: LANDDIS.PRN

(Lambert conformal projection)

1995 MAY 28 18:18:43.98

Fig. LAND-Adj-50-MAX (Col. X)

Group 4. Ground Motion with NEHRP Adjustment

Fig. NRDG-NHRP-50-V (Col. AF)


Fig. NRDG-NHRP-50-MAX (Col. AH)

Fig. WHIT-NHRP-50-V (Col. AF)

Fig. WHIT-NHRP-50-MAX (Col. AH)

Fig. LAND-NHRP-50-V (Col. AF)

Fig. LAND-NHRP-50-MAX (Col. AH)



Northridge Earthquake M=6.6 of January 17, 1994

Vertical NEHRP Adjusted Acceleration, g

RADIUS OF CIRCLE IS 50 KM

Stations - total: 348, with data: 303, without: 45, rejected: 0, in plot: 171

Map File: CALINE2.DAT

Command File: NR50VN.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: NRDGDIS.PRN

(Lambert conformal projection)

1995 MAY 28 18:20:18.57

Fig. NRDG-NHRP-50-V (Col. AF)



Northridge Earthquake M=6.6 of January 17, 1994

NEHRP Adjusted Maximum Horizontal Acceleration, g

RADIUS OF CIRCLE IS 50 KM

Stations -- total: 348, with data: 344, without: 4, rejected: 0, in plot: 200

Map File: CALINE2.DAT

Command File: NR50HN.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: NRDGDIS.PRN

(Lambert conformal projection)

1995 MAY 28 18:23:20.43

Fig. NRDG-NHRP-50-MAX (Col. AH)



Whittier Earthquake M=6.1 of October 1, 1987

Vertical NEHRP Adjusted Acceleration, g

RADIUS OF CIRCLE IS 50 KM

Stations - total: 184, with data: 184, without: 0, rejected: 0, in plot: 116

Map File: CALINE2.DAT

Command File: WH50VN.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: WHITDIS.PRN

(Lambert conformal projection)

1995 MAY 28 18:27:32.15

Fig. WHIT-NHRP-50-V (Col. AF)



Whittier Earthquake M=6.1 of October 1, 1987

NEHRP Adjusted Maximum Horizontal Acceleration, g

RADIUS OF CIRCLE IS 50 KM

Stations - total: 184, with data: 184, without: 0, rejected: 0, in plot: 116

Map File: CALINE2.DAT


Command File: WH50HN.GAC

Program: APGFAC2.75

Fault File: KANAMN.DAT

Station File: WHITDIS.PRN
(Lambert conformal projection)
1995 MAY 28 18:28:49.98

Fig. WHIT-NHRP-50-MAX (Col. AH)



Landers Earthquake M=7.5 of June 28, 1992

Vertical NEHRP Adjusted Acceleration, g

RADIUS OF CIRCLE IS 50 KM

Stations - total: 162, with data: 162, without: 0, rejected: 0, in plot: 29

Map File: CALINE2.DAT

Command File: LN50VN.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: LANDDIS.PRN

(Lambert conformal projection)

1995 MAY 28 18:24:48.72

Fig. LAND-NHRP-50-V (Col. AF)



Landers Earthquake M=7.5 of June 28, 1992

NEHRP Adjusted Maximum Horizontal Acceleration, g

RADIUS OF CIRCLE IS 50 KM

Stations - total: 162, with data: 162, without: 0, rejected: 0, in plot: 29

Map File: CALINE2.DAT

Command File: LN50HN.GAC

Program: APGFAC2.75

Fault File: KANAMN.DAT

Station File: LANDDIS.PRN
(Lambert conformal projection)

1995 MAY 28 18:28:08.17

Fig. LAND-NHRP-50-MAX (Col. AH)

Group 5. Ground Motion with NEHRP plus Structural Adjustment

Fig NRDG-NHRP/Str-50-V (Col. AN)


Fig NRDG-NHRP/Str-50-MAX (Col. AP)

Fig. WHIT-NHRP/Str-50-V (Col. AN)

Fig. WHIT-NHRP/Str-50-MAX (Col. AP)

Fig. LAND-NHRP/Str-50-V (Col. AN)

Fig. LAND-NHRP/Str-50-MAX (Col. AP)



Northridge Earthquake M=6.6 of January 17, 1994

Vertical NEHRP+Structure Corrected Acceleration, g

RADIUS OF CIRCLE IS 50 KM


Stations - total: 348, with data: 308, without: 40, rejected: 0, in plot: 173

Map File: CALINE2.DAT
Command File: NR50VS.GAC
Program: APGFAC2.75

Fault File: KANAMN.DAT

Station File: NRDGDIS.PRN
(Lambert conformal projection)
1995 MAY 28 18:31:39.76

Fig. NRDG-NHRP/Str-50-V (Col. AN)



Northridge Earthquake M=6.6 of January 17, 1994
NEHRP+Structure Corrected Maximum Horizontal Acceleration, g
RADIUS OF CIRCLE IS 50 KM


Stations - total: 348, with data: 343, without: 5, rejected: 0, in plot: 199

Map File: CALINE2.DAT
 Command File: NR50HS.GAC
 Program: APGFAC2.75

Fault File: KANAMN.DAT

Station File: NRGDGDIS.PRN
 (Lambert conformal projection)
 1995 MAY 28 18:34:38.81

Fig. NRDG-NHRP/Str-50-MAX (Col. AP)



Whittier Earthquake M=6.1 of October 1, 1987
 NEHRP+Structure Corrected Maximum Horizontal Acceleration, g
 RADIUS OF CIRCLE IS 50 KM

Stations - total: 184, with data: 184, without: 0, rejected: 0, in plot: 116

Map File: CALINE2.DAT

Command File: WH50HS.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: WHITDIS.PRN

(Lambert conformal projection)

1995 MAY 28 18:40:50.55

Fig. WHIT-NHRP/Str-50-MAX (Col. AP)



Landers Earthquake M=7.5 of June 28, 1992

Vertical NEHRP+Structure Corrected Acceleration, g

RADIUS OF CIRCLE IS 50 KM

Stations - total: 162, with data: 162, without: 0, rejected: 0, in plot: 29

Map File: CALINE2.DAT

Command File: LN50VS.GAC

Program: APGFAC2.75


Fault File: KANAMN.DAT

Station File: LANDDIS.PRN

(Lambert conformal projection)

1995 MAY 28 18:36:06.20

Fig. LAND-NHRP/Str-50-V (Col. AN)



Landers Earthquake M=7.5 of June 28, 1992
 NEHRP+Structure Corrected Maximum Horizontal Acceleration, g
 RADIUS OF CIRCLE IS 50 KM

Stations - total: 162, with data: 162, without: 0, rejected: 0, in plot: 29

Map File: CALINE2.DAT

Command File: LN50HS.GAC

Program: APGFAC2.75

Fault File: KANAMN.DAT

Station File: LANDDIS.PRN

(Lambert conformal projection)

1995 MAY 28 18:37:29.30

Fig. LAND-NHRP/Str-50-MAX (Col. AP)

REPORT DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.

1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE February 1998	3. REPORT TYPE AND DATES COVERED Final report	
4. TITLE AND SUBTITLE A Study of Near-Source Earthquake Ground Motions of Three California Earthquakes: Northridge, Whittier, and Landers			5. FUNDING NUMBERS	
6. AUTHOR(S) David J. Leeds				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) David J. Leeds and Associates 11972 Chalon Road Los Angeles, CA 90049			8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Corps of Engineers, Washington, DC 20314-1000; U.S. Army Engineer Waterways Experiment Station, 3909 Halls Ferry Road, Vicksburg, MS 39180-6199			10. SPONSORING/MONITORING AGENCY REPORT NUMBER Contract Report GL-98-2	
11. SUPPLEMENTARY NOTES Available from National Technical Information Service, 5285 Port Royal Road, Springfield, VA 22161.				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Approved for public release; distribution is unlimited.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) Three datasets were analyzed and maps were prepared of near-source ground motions associated with the Whittier, Northridge, and Landers earthquakes in southern California. Vertical motions were enhanced in the near-source area of high-angle thrust faults at Whittier and Landers, similar to Northridge. Factors are provided for the enhancement in terms of site conditions. Distance factors were established with vertical-to-horizontal ratios. Areal patterns of earthquake ground motions were plotted with relation to known faults.				
14. SUBJECT TERMS Blind faults Ground motions Landers earthquake Northridge earthquake Whittier earthquake			15. NUMBER OF PAGES 68	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT UNCLASSIFIED	18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED	19. SECURITY CLASSIFICATION OF ABSTRACT	20. LIMITATION OF ABSTRACT	